



UTIFORM

Plastering Machines _ Screed Pumps

Utiform UK

Siloform G

[Call for Pricing](#)

Siloform G Conveying System Characteristics

FEATURES:

- Conveying system for premixed mortar from free fall silos.
- CE 98/37.

BENEFITS:

- Reduces labour costs and material losses.
- Standar silo connection DN 250.
- High transport distances 120 - 180 meters depending on the compressor.

ADVANTAGES:

- Machine does not depend on weather conditions.

Standard equipment:

- Electric compressor.
- Electric control box.
- Protection hood.
- Warranty Certificate.
- CE Certificate.
- Instruction manual and parts book.

Recommended equipment:

- 2 x 25 m transport hose Dn 38
- 50 m sensor hose 3 x 1,5 mm²
- 25 m electric hose 5 x 2,5 mm²
- Electric sensor 42 V - 3 poles.
- Insulflation hood.

Technical data :

Power of rotary compressor motor	5,5 Kw - 400 V - 50Hz
Air flow with pressure of 2 bar	100 m ³ /h
Maximum over-pressure	2,8 bar
Maximum distance	approx.150 m
Tank capacity	approx. 70 l
Tank weight	approx. 59 Kg
Size LxWxH (mm)	1060 x 470 x 530

[Vendor Information](#)

Customer Reviews: There are yet no reviews for this product.

Please log in to write a review.